



**DUMP TRUCKS SECTION - RIDGED- ARTICULATED HAULERS- TRACKED- SITE**

**ARTICULATED AND RIDGED DUMP TRUCKS**

<b>ASTRA -Ridged Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
RD28					NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
RD32					Ditto
RD38	D7060 or D8070	D8087	D8099 VRS		Ditto
RD40	D7060 or D8070	D8087	D8099 VRS		Ditto
<b>AVELING BARFORD - Ridged Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
RDO30	D7060 or D8070	D8087	D8099 VRS	KAB301	NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
RDO50	D7060 or D8070	D8087	D8099 VRS	KAB301	Ditto
RDO 55	D7060 or D8070	D8087	D8099 VRS	KAB301	Ditto
RDO 255	D7060 or D8070	D8087	D8099 VRS	KAB301	Ditto
<b>BELLOLI- Ridged Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
DM322	D7060 or D8070	D8087	D8099 VRS		NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
<b>CATERPILLAR- Ridged Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
768	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	If replacing a CAT Contour or Comfort seat (bolt pattern 395mm x 402mm). Kit SA19236.901 is required. Unless a D5087 or D8087 is used (direct replacement)
769	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	Ditto
771D	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	Ditto
772	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	Ditto
773B	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	Ditto
733C	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	Ditto
773D	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	Ditto
775D	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	Ditto
777D	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	Ditto
784	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	Ditto
785B	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	Ditto
789B	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	Ditto
793B	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	Ditto
797					

<b>FIAT-HITACHI- Ridged Dump trucks</b>					
<b>MODEL</b>	<b>OPTION 1</b>	<b>OPTION 2</b>	<b>OPTION 3 (Air Option)</b>	<b>OEM SEAT</b>	<b>COMMENTS</b>
AD30	D7060 or D8070	D8087	D8099 VRS	KAB515	NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
<b>EUCLID- Ridged Dump trucks</b>					
<b>MODEL</b>	<b>OPTION 1</b>	<b>OPTION 2</b>	<b>OPTION 3 (Air Option)</b>	<b>OEM SEAT</b>	<b>COMMENTS</b>
Euclid R32	D7060 or D8070	D8087	D8099 VRS	6000/575 or KAB525	Note: SD or R seat version are the only seats recommended for mining applications. 1. If factory seat is the isringhausen 6000/575, use height rise kit SA19178 with SA19096.901. Factory pattern: 8.5" w x 12.75". 2. If factory seat is isringhausen air suspension, use SA19096.901. Factory bolt pattern: 11" w x 12.75". NOTE:Sears seats cannot be used if factory seat is fitted with joystick bracket.
Euclid R35	D7060 or D8070	D8087	D8099 VRS	6000/575 or KAB525	Ditto
Euclid R36	D7060 or D8070	D8087	D8099 VRS	6000/575 or KAB525	Ditto
Euclid R40	D7060 or D8070	D8087	D8099 VRS	6000/575 or KAB525	Ditto
Euclid R60	D7060 or D8070	D8087	D8099 VRS	6000/575 or KAB525	Ditto
Euclid R65	D7060 or D8070	D8087	D8099 VRS	6000/575 or KAB525	Ditto
Euclid R85	D7060 or D8070	D8087	D8099 VRS	6000/575 or KAB525	Ditto
Euclid R90	D7060 or D8070	D8087	D8099 VRS	6000/575 or KAB525	Ditto
Euclid R130	D7060 or D8070	D8087	D8099 VRS	6000/575 or KAB525	Ditto
Euclid R150	D7060 or D8070	D8087	D8099 VRS	6000/575 or KAB525	Ditto
Euclid R160	D7060 or D8070	D8087	D8099 VRS	6000/575 or KAB525	Ditto
Euclid R170	D7060 or D8070	D8087	D8099 VRS	6000/575 or KAB525	Ditto
Euclid R190	D7060 or D8070	D8087	D8099 VRS	6000/575 or KAB525	Ditto
Euclid R260	D7060 or D8070	D8087	D8099 VRS	6000/575 or KAB525	Ditto
<b>HITACHI -EUCLID- Ridged Dump trucks</b>					
<b>MODEL</b>	<b>OPTION 1</b>	<b>OPTION 2</b>	<b>OPTION 3 (Air Option)</b>	<b>OEM SEAT</b>	<b>COMMENTS</b>
EH600	D7060 or D8070	D8087	D8099 VRS		NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
EH650	D7060 or D8070	D8087	D8099 VRS		Ditto
EH700	D7060 or D8070	D8087	D8099 VRS		Ditto
EH750	D7060 or D8070	D8087	D8099 VRS		Ditto
EH1000	D7060 or D8070	D8087	D8099 VRS		Ditto
EH1100	D7060 or D8070	D8087	D8099 VRS		Ditto
EH1600	D7060 or D8070	D8087	D8099 VRS		Ditto
EH1700	D7060 or D8070	D8087	D8099 VRS		Ditto
EH3000	D7060 or D8070	D8087	D8099 VRS		Ditto
EH3500	D7060 or D8070	D8087	D8099 VRS		Ditto
EH4000	D7060 or D8070	D8087	D8099 VRS		Ditto
EH4500	D7060 or D8070	D8087	D8099 VRS		Ditto
EH5000	D7060 or D8070	D8087	D8099 VRS		Ditto

<b>KOMATSU- Ridged Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
					NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
HD985-3	D7060 or D8070	D8087	D8099 VRS	KAB525 or ISRI	
HD785-5	D7060 or D8070	D8087	D8099 VRS	KAB525 or ISRI	Ditto
HD605-5	D7060 or D8070	D8087	D8099 VRS	KAB525 or ISRI	Ditto
HD465-5	D7060 or D8070	D8087	D8099 VRS	KAB525 or ISRI	Ditto
HD405-6	D7060 or D8070	D8087	D8099 VRS	KAB525 or ISRI	Ditto
HD325-6 4WD	D7060 or D8070	D8087	D8099 VRS	KAB525 or ISRI	Ditto
HD325-6	D7060 or D8070	D8087	D8099 VRS	KAB525 or ISRI	Ditto
HD325	D7060 or D8070	D8087	D8099 VRS	KAB525 or ISRI	Ditto
210M	D7060 or D8070	D8087	D8099 VRS	KAB525 or ISRI	Ditto
330M	D7060 or D8070	D8087	D8099 VRS	KAB525 or ISRI	Ditto
530M	D7060 or D8070	D8087	D8099 VRS	KAB525 or ISRI	Ditto
630E	D7060 or D8070	D8087	D8099 VRS	KAB525 or ISRI	Ditto
685E	D7060 or D8070	D8087	D8099 VRS	KAB525 or ISRI	Ditto
730E	D7060 or D8070	D8087	D8099 VRS	KAB525 or ISRI	Ditto
830E	D7060 or D8070	D8087	D8099 VRS	KAB525 or ISRI	Ditto
930E	D7060 or D8070	D8087	D8099 VRS	KAB525 or ISRI	Ditto
HA250	D7060 or D8070	D8087	D8099 VRS	KAB525 or ISRI	Ditto
HA270	D7060 or D8070	D8087	D8099 VRS	KAB525 or ISRI	Ditto
<b>LIEBHERR- Ridged Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
					NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
T252	<b>D7060</b>	<b>D8087</b>	<b>D8099VRS</b>		Ditto
T262	<b>D7060</b>	<b>D8087</b>	<b>D8099VRS</b>		Ditto
T282	<b>D7060</b>	<b>D8087</b>	<b>D8099VRS</b>		Ditto
T1274	<b>D7060</b>	<b>D8087</b>	<b>D8099VRS</b>		Ditto
<b>NORDSTROM- Ridged Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
					NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
666B	D7060 or D8070	D8087	D8099 VRS		Ditto
666 6X4	D7060 or D8070	D8087	D8099 VRS		Ditto
<b>O &amp; K- Ridged Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
					NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
K55B	D7060 or D8070	D8087	D8099 VRS	ISRI	
K40-4	D7060 or D8070	D8087	D8099 VRS	ISRI	Ditto
BD220	D7060 or D8070	D8087	D8099 VRS	ISRI	Ditto
BD240	D7060 or D8070	D8087	D8099 VRS	ISRI	Ditto
BD720	D7060 or D8070	D8087	D8099 VRS	ISRI	Ditto
MT5500	D7060 or D8070	D8087	D8099 VRS	ISRI	Ditto
MT4400	D7060 or D8070	D8087	D8099 VRS	ISRI	Ditto
MT3700	D7060 or D8070	D8087	D8099 VRS	ISRI	Ditto
MT3600	D7060 or D8070	D8087	D8099 VRS	ISRI	Ditto
MT3300	D7060 or D8070	D8087	D8099 VRS	ISRI	Ditto
MT3000	D7060 or D8070	D8087	D8099 VRS	ISRI	Ditto

<b>PAYHAULER TEREX - Articulated &amp; Ridged Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
350C	D7060 or D8070	D8087	D8099 VRS		NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
<b>PERLINI- Articulated &amp; Ridged Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
7133	D7060 or D8070	D8087	D8099 VRS		NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
DP255	D7060 or D8070	D8087	D8099 VRS	BE GE	Ditto
DPT305	D7060 or D8070	D8087	D8099 VRS	BE GE	Ditto
DP405	D7060 or D8070	D8087	D8099 VRS	BE GE	Ditto
DP605	D7060 or D8070	D8087	D8099 VRS	BE GE	Ditto
DP705	D7060 or D8070	D8087	D8099 VRS	BE GE	Ditto
DP905	D7060 or D8070	D8087	D8099 VRS	BE GE	Ditto
<b>THWAITES- Articulated Dump Trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
TD12	D7060 or D8070	D8087	D8099 VRS	Grammer	NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
<b>TEREX- Ridged Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
TR35	D7060 or D8070	D8087	D8099 VRS	KAB555 or Sears D8087	NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
TR40	D7060 or D8070	D8087	D8099 VRS	KAB555 or Sears D8087	Ditto
TR45	D7060 or D8070	D8087	D8099 VRS	KAB555 or Sears D8087	Ditto
TR60	D7060 or D8070	D8087	D8099 VRS	KAB555 or Sears D8087	Ditto
TR70	D7060 or D8070	D8087	D8099 VRS	KAB555 or Sears D8087	Ditto
TR100	D7060 or D8070	D8087	D8099 VRS	KAB555 or Sears D8087	Ditto
TR200	D7060 or D8070	D8087	D8099 VRS	KAB555 or Sears D8087	Ditto
<b>UNIT RIG- TEREX- Ridged Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
MT3300	D8060or D8070	D8087	D8099VRS		NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
MT3600	D8060or D8070	D8087	D8099VRS		
MT3700	D8060or D8070	D8087	D8099VRS		
MT4400	D8060or D8070	D8087	D8099VRS		
MT5500	D8060or D8070	D8087	D8099VRS		
MT6300	D8060or D8070	D8087	D8099VRS		
BD270	D8060or D8070	D8087	D8099VRS		

<b>WAGNER- Dumpers</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
W26	D7060 or D8070	D8087	D8099 VRS		NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
W13	D7060 or D8070	D8087	D8099 VRS		
<b>ARTICULATED HAULERS</b>					
<b>RECOMMENDED REPLACEMENT SEATING</b>					
<b>ASTRA- Articulated Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
ADT25	D7060 or D8070	D8087	D8099 VRS		NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor. 52 is a direct fit.
ADT30	D7060 or D8070	D8087	D8099 VRS		
ADT35	D7060 or D8070	D8087	D8099 VRS		
ADT40	D7060 or D8070	D8087	D8099 VRS		
<b>BELL- Articulated Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
B25C	8052 or D8060	D8087	D8099 VRS	Seats, Grammer, Se	NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor. 52 is a direct fit.
B30C	8052 or D8060	D8087	D8099 VRS		
B35	8052 or D8060	D8087	D8099 VRS	Seats, Grammer, Se	
B40	8052 or D8060	D8087	D8099 VRS	Seats, Grammer, Se	
<b>CASE- Articulated Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
325	D7060 or D8070	D8087	D8099 VRS		NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor. 52 is a direct fit.
330	D7060 or D8070	D8087	D8099 VRS		
<b>CATERPILLAR- Articulated Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
725	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	If replacing a CAT Contour or Comfort seat (bolt pattern 395mm x 402mm). Kit SA19236.901 is required. Unless a D5087 or D8087 is used (direct replacement)
730	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	
735	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	
740	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	
D20D	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	
D25D	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	
D30D	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	
D35	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	
D40D	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	
D250E	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	
D330B	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	
D300E	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	
D350E	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	
D400E	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	
D500	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	
D550	D7060 or D8070	D8087	D8099 VRS	Sears/CAT Contour	

<b>EUCLID, Articulated Dump trucks</b>						
<b>MODEL</b>	<b>OPTION 1</b>	<b>OPTION 2</b>	<b>OPTION 3 (Air Option)</b>	<b>OEM SEAT</b>	<b>COMMENTS</b>	
R32 Euclid	D7060 or D8070	D8087	D8099 VRS	KAB525	NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.	
R35 Euclid	D7060 or D8070	D8087	D8099 VRS	KAB525		
R36 Euclid	D7060 or D8070	D8087	D8099 VRS	KAB525		
R40 Euclid	D7060 or D8070	D8087	D8099 VRS	KAB525		
R60 Euclid	D7060 or D8070	D8087	D8099 VRS	KAB525		
R65 Euclid	D7060 or D8070	D8087	D8099 VRS	KAB525		
R85 Euclid	D7060 or D8070	D8087	D8099 VRS	KAB525		
R90 Euclid	D7060 or D8070	D8087	D8099 VRS	KAB525		
R130 Euclid	D7060 or D8070	D8087	D8099 VRS	KAB525		
R150 Euclid	D7060 or D8070	D8087	D8099 VRS	KAB525		
R160 Euclid	D7060 or D8070	D8087	D8099 VRS	KAB525		
R170 Euclid	D7060 or D8070	D8087	D8099 VRS	KAB525		
R190 Euclid	D7060 or D8070	D8087	D8099 VRS	KAB525		
R260 Euclid	D7060 or D8070	D8087	D8099 VRS	KAB525		
<b>FIAT-HITACHI, Articulated Dump trucks</b>						
<b>MODEL</b>	<b>OPTION 1</b>	<b>OPTION 2</b>	<b>OPTION 3 (Air Option)</b>	<b>OEM SEAT</b>		<b>COMMENTS</b>
AD30	D7060 or D8070	D8087	D8099 VRS	KAB515		
<b>HITACHI, Articulated Dump trucks</b>						
<b>MODEL</b>	<b>OPTION 1</b>	<b>OPTION 2</b>	<b>OPTION 3 (Air Option)</b>	<b>OEM SEAT</b>	<b>COMMENTS</b>	
AH250	8052 or D8060	D8087	D8099 VRS	Seats, Grammer/ Sears/	NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.	
AH300	8052 or D8060	D8087	D8099 VRS	Seats, Grammer/ Sears/		
AH350	8052 or D8060	D8087	D8099 VRS	Seats, Grammer/ Sears/		
AH400	8052 or D8060	D8087	D8099 VRS	Seats, Grammer/ Sears/		
<b>HYDREMA, Articulated &amp; Ridged Dump trucks</b>						
<b>MODEL</b>	<b>OPTION 1</b>	<b>OPTION 2</b>	<b>OPTION 3 (Air Option)</b>	<b>OEM SEAT</b>	<b>COMMENTS</b>	
910	D7060 or D8070	D8087	D8099 VRS		NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.	
912	D7060 or D8070	D8087	D8099 VRS			
<b>JCB, Articulated Dump trucks</b>						
<b>MODEL</b>	<b>OPTION 1</b>	<b>OPTION 2</b>	<b>OPTION 3 (Air Option)</b>	<b>OEM SEAT</b>	<b>COMMENTS</b>	
714	D7060 or D8070	D8087	D8099 VRS		NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.	
712	D7060 or D8070	D8087	D8099 VRS			
<b>700</b>	D7060 or D8070	D8087	D8099 VRS			

<b>KOMATSU/ HAULPAK-Articulated Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
HA250	D7060 or D8070	D8087	D8099 VRS	6000/575 or 6000/577	NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
HA270	D7060 or D8070	D8087	D8099 VRS	6000/575 or 6000/577	
HM300	D7060 or D8070	D8087	D8099 VRS		
HM350	D7060 or D8070	D8087	D8099 VRS		
HM400	D7060 or D8070	D8087	D8099 VRS		
<b>LIEBHERR, Ridged Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
262	D7060 or D8070	D8087	D8099 VRS	6000/575 or 6000/577	NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
<b>MOXY - Articulated Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
6200					NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
6225B	D7060 or D8070	D8087	D8099 VRS		
5222B	D7060 or D8070	D8087	D8099 VRS		
5225B	D7060 or D8070	D8087	D8099 VRS		
MT26	D7060 or D8070	D8087	D8099 VRS		
MT27	D7060 or D8070	D8087	D8099 VRS		
MT30	D7060 or D8070	D8087	D8099 VRS		
	D7060 or D8070	D8087	D8099 VRS		
MT31	D7060 or D8070	D8087	D8099 VRS		
<b>NEW HOLLAND - Articulated Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
<b>SAMSUNG - Articulated Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
130W	D7060 or D8070	D8087	D8099 VRS		NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
210C	D7060 or D8070	D8087	D8099 VRS		

<b>TEREX- Articulated Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
2366	D7060 or D8070	D8087	D8099 VRS	KAB525	NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
2566C	D7060 or D8070	D8087	D8099 VRS	KAB525	1. KAB 555 is the factory seat in late model machines. Installation kit SA19096.901 is required. if KAB 555 mounting pattern: 11" w x 13".
2766C	D7060 or D8070	D8087	D8099 VRS	KAB525	Ditto
	D7060 or D8070	D8087	D8099 VRS	KAB525	Ditto
3066C	D7060 or D8070	D8087	D8099 VRS	KAB525	Ditto
3305B	D7060 or D8070	D8087	D8099 VRS	KAB525	Ditto
3305	D7060 or D8070	D8087	D8099 VRS	KAB525	Ditto
3307	D7060 or D8070	D8087	D8099 VRS	KAB525	Ditto
3309	D7060 or D8070	D8087	D8099 VRS	KAB525	Ditto
3310	D7060 or D8070	D8087	D8099 VRS	KAB525	Ditto
3311	D7060 or D8070	D8087	D8099 VRS	KAB525	Ditto
3314	D7060 or D8070	D8087	D8099 VRS	KAB525	Ditto
3333	D7060 or D8070	D8087	D8099 VRS	KAB525	Ditto
3335**	D7060 or D8070	D8087	D8099 VRS	KAB525	Ditto
3340**	D7060 or D8070	D8087	D8099 VRS	KAB525	Ditto
3360B**	D7060 or D8070	D8087	D8099 VRS	KAB525	Ditto
3310E**	D7060 or D8070	D8087	D8099 VRS	KAB525	Ditto
33100B**	D7060 or D8070	D8087	D8099 VRS	KAB525	Ditto
4066C**	D7060 or D8070	D8087	D8099 VRS	KAB525	Ditto
** - LATE MODELS	D7060 or D8070	D8087	D8099 VRS	KAB525	Ditto
TA25	D7060 or D8070	D8087	D8099 VRS	KAB555 or MSG95/520	Ditto
TA30	D7060 or D8070	D8087	D8099 VRS	KAB555 or MSG95/520	Ditto
TA35	D7060 or D8070	D8087	D8099 VRS	KAB555 or MSG95/520	Ditto
TA40	D7060 or D8070	D8087	D8099 VRS	KAB555 or MSG95/520	Ditto
<b>TAMROCK (TORO)- Articulated Dump truck</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
SUPRA 0012H	D7060 or D8070	D8087	D8099 VRS		NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
50D	D7060 or D8070	D8087	D8099 VRS		Ditto
301D	D7060 or D8070	D8087	D8099 VRS		Ditto
400D	D7060 or D8070	D8087	D8099 VRS		Ditto
450D	D7060 or D8070	D8087	D8099 VRS		Ditto
500D	D7060 or D8070	D8087	D8099 VRS		Ditto
501D	D7060 or D8070	D8087	D8099 VRS		Ditto
<b>SAMSUNG-Articulated Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
210C	D7060 or D8070	D8087	D8099 VRS		NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
130W	D7060 or D8070	D8087	D8099 VRS		Ditto
<b>VOLVO- Articulated Dump trucks</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3 (Air Option)	OEM SEAT	COMMENTS
A25B	D7060 or D8070	D8087	D8099 VRS	ISRI or BE GE	NOTE: 87 SUSPENSIONS versions are the only seats recommended for mining applications. Installation kit SA19096.901 required. For 60 & 70 series suspensions This kit accommodates all bolt patterns up to 355 wide x 395mm (14 x15.5"). 87 & 99 series suspensions will require new mounting holes in cab floor.
A25C	D7060 or D8070	D8087	D8099 VRS	ISRI or BE GE	Ditto
A30	D7060 or D8070	D8087	D8099 VRS	ISRI or BE GE	Ditto
A30C	D7060 or D8070	D8087	D8099 VRS	ISRI or BE GE	Ditto
A35	D7060 or D8070	D8087	D8099 VRS	ISRI or BE GE	Ditto
A20	D7060 or D8070	D8087	D8099 VRS	ISRI or BE GE	Ditto
A40	D7060 or D8070	D8087	D8099 VRS	ISRI or BE GE	Ditto
A40C	D7060 or D8070	D8087	D8099 VRS		Ditto

**SITE DUMPERS**

**RECOMMENDED REPLACEMENT SEATING**

<b>AMMAN YANMAR Site dumpers</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3	OEM SEAT	COMMENTS
2500	706	906			
<b>AUSA Site dumpers</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3	OEM SEAT	COMMENTS
35MTG	907	1407			
<b>BARFORD Site dumpers</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3	OEM SEAT	COMMENTS
SX9000	706	906		Sears/ Pilot	Direct replacement
SXR8000	706	906		Sears/ Pilot	Direct replacement
SX8000	706	906		Sears/ Pilot	Direct replacement
SXR7000	706	906		Sears/ Pilot	Direct replacement
SX7000	706	906		Sears/ Pilot	Direct replacement
SXR6000	706	906		Sears/ Pilot	Direct replacement
SX6000	706	906		Sears/ Pilot	Direct replacement
SX5000	706	906		Sears/ Pilot	Direct replacement
SXR5000	706	906		Sears/ Pilot	Direct replacement
SXR4000	706	906		Sears/ Pilot	Direct replacement
SXR3000	706	906		Sears/ Pilot	Direct replacement
SX3000	706	906		Sears/ Pilot	Direct replacement
SX2000	706	906		Sears/ Pilot	Direct replacement
<b>BENFORD site dumpers</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3	OEM SEAT	COMMENTS
TS	706 or 1500	906 or 1500		DS44/MSG20	Fitting not confirmed
TT	706 or 1500	906 or 1500			
<b>LIFTON site dumpers</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3	OEM SEAT	COMMENTS
LS500	706	906			Fitting not confirmed
LS2000	706	906			Fitting not confirmed
LS2700	706	906			Fitting not confirmed
LS4500					
850					
1200F					
1200S					
<b>MOROOKA site dumpers</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3	OEM SEAT	COMMENTS
MST3000	706	906			Fitting not confirmed
MST2600	706	906			Fitting not confirmed
MST2200	706	906			Fitting not confirmed
MST2000	706	906			Fitting not confirmed
MST1500	706	906			Fitting not confirmed
MST700	706	906			Fitting not confirmed
MST600	706	906			Fitting not confirmed
<b>MULTIDRIVE site dumpers</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3	OEM SEAT	COMMENTS
180	3007				Fitting not confirmed
<b>PICCINI site dumpers</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3	OEM SEAT	COMMENTS
					Fitting not confirmed
<b>THWAITES Site dumpers</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3	OEM SEAT	COMMENTS
TD12					
GIANT					
GOLIATH					
série 2000					
série 9000				MSG20	Fitting not confirmed
<b>WINGET Site dumpers</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3	OEM SEAT	COMMENTS
4S 2500RS				XH2/P2	
4B 2000				P2	
<b>YANMAR Site dumpers</b>					
MODEL	OPTION 1	OPTION 2	OPTION 3	OEM SEAT	COMMENTS
2500					Fitting not confirmed